

4.1.75 Aircraft safe for maintenance F-5A

IDBoø.3.FF.1.5.39

Ver.5.00

Side: 1 av 2

CHECKPOINTS	SIGN
Install MLG chocks (<i>N/A if aircraft is on fuselage jacks</i>)	
Statically ground aircraft	
Place oil/fuel spillage container under aircraft	
Install NLG safety pin (1)	
Install MLG safety pins (2)	
Install pitot cover (1)	
Arresting hook lowered or safety pin installed	
Install ejection seat safety pins (1)	
Disconnect aircraft battery	N/A
Install engine inlet covers	
Install dragchute safetypins	
Check jacks for correct position for LG operation	
Check gear doors switch position (OPEN)	
Check lock safety ring on jacks for right position	
HUD EU fuse – Pulled	
HUD FAN fuse – Pulled	
All HEATER fuses in cockpit – Pulled	
FUEL BOOST PUMP L/H and R/H, crossfeed switch - Off	
FUEL SHUT-OFF L/H, R/H closed position with guard down	
Check that Flap position corresponds to Flap switch position	
All other cockpit switches in OFF/NORMAL position	
<i>Before applying Hydraulic power:</i>	
Ensure clearance to equipment and obstacles, set out Cone barrier and Red Warning light.	

Date: _____ SIGN: _____

Interne referanser

Eksterne referanser